

3083

1. 基本物性 BASIC PROPERTIES

主要成分 Composition

橡胶溶剂 Rubber solvent	30-40%
乙酸乙酯 Ethyl acetate	10-15%
碳酸二甲酯 Dimethyl carbonate	10-15%
合成橡胶 Synthetic Rubber	15-20%
合成树脂 Synthetic Resin	30-35%

外观: 淡黄色透明粘稠液

Appearance: Light yellow viscous liquid

固成份 Solid content: 35-45%

粘度 Viscosity (25°C) : 150-250 cps

保存期限: 6 个月

Shelf life: 6 months

2. 用途 APPLICATIONS

3083 为无甲苯喷胶, 应用于鞋面 (布、真皮内里、泡棉和 Counter 等)。

3083 is a toluene-free spraying adhesive applied in attaching upper (cloth, leather lining, foam and counter).

3. 特性 PROPERTIES

开放时间长, 耐黄变可达 4 级。

Long tack time, yellowing performance is up to level 4.

4. 流程 APPLICATION PROCESS



清洁鞋材表面，必要时请处理鞋底和鞋面，干燥后送机器喷胶。

Clean surface and/or apply primer to sole and upper if necessary. Apply adhesive.

干燥时间：自然干燥 1-5 分钟，贴合、压合。

Drying time: Dry for 1-5 min at R. T., then attaching & pressing.

以上操作条件仅供参考，应视生产线实际条件而调整。

The above condition is for reference only. The actual conditions should be set and adjusted according to the actual production facilities.

5. 注意事项 PRECAUTIONS

易燃液体。禁止明火。

Highly flammable liquid. No open flames.

使用后盖紧容器。

Close the container air tight after use.

储存于阴凉干爽的地方 (5-40°C)。

Store at dry and cool place with good ventilation. Make sure the temperature is between 5-40°C.

详细资料请参考 MSDS。

Please refer to MSDS for more details.

6. 包装规格 PACKING

铁桶：15 公斤/桶。

Tin: 15 kg/tin.